



XINGTAI AGRICULTURAL MACHINERY CO., LTD



YOUR IDEAL TRACTOR PARTNER.

Xingtai Agricultural Machinery Co., Ltd. was established in 2003 and is a professional manufacturer specializing in the production of small and medium-sized tractors and agricultural machinery.

 XT-AGRO.com

 info@xt-agro.com

 +86 187 3095 8917

 No. 608, Ping'an Street, Nanhe District, Xingtai City, Hebei Province, China



XINGTAI AGRICULTURAL MACHINERY CO., LTD

Our Services

We provide comprehensive services to support our customers and partners worldwide. From product selection to after-sales support, we focus on delivering reliable solutions and long-term value.

- * Product Customization – Multiple configurations available to meet different market and farming needs
- * OEM & Branding Support – Logo, color, and packaging customization supported
- * Spare Parts Supply – Stable and long-term spare parts availability
- * Technical Support – Operation guidance and maintenance assistance

With professional service and responsive support, we help our partners grow their business with confidence.





XINGTAI AGRICULTURAL MACHINERY CO., LTD



MODEL : XT-CLASSIC

The XT-Classic series is equipped with a vertical single-cylinder diesel engine combined with a direct gear transmission system, designed for durability and long-term operation in tough farming conditions.

- * Strong and stable power output for continuous operation
- * No belt slipping, suitable for heavy load and rough fields
- * Lower maintenance cost and longer service life
- * Easy operation and repair, ideal for local mechanics

With its simple structure, reliable gear drive, and easy maintenance, the XT-Classic tractor is an ideal solution for farmers seeking a durable, cost-effective machine for small and medium-scale agriculture.



XINGTAI AGRICULTURAL MACHINERY CO., LTD

MODEL : XT-CLASSIC

XingTai Series Tractor XT-140/160/180/200		
Specifications		
Model	XT-140/160/180/200	
Drive Type	Rear Wheel Drive (4x2)	
Gearbox Type	XT	
Transmission Type	6 Forward & 2 Reverse gears	
Engine	Model	DLH195/1100/1105/1110
	Type	Diesel , Vertical , 1-Cylinder , 95/100/105/110mm-Bore , 4-Stroke , Water-Cooled
	Rated Speed	2200rpm
	12-hour Rated Power	9.4/11.7/13.2/14.5kW
	Displacement	0.8/0.9/1.0L
	Emission	Stage-2
	Starting System	Electric
Clutch Type	8-inch Single-stage Clutch	
Overall Dimensions	Length	2350mm
	Width	1200mm
	Height	1750mm
Wheelbase	1430mm	
Wheel Size	Front Wheel	4.00-14
	Rear Wheel	7.50-20
Wheel Track	Front Wheel	960mm
	Rear Wheel	980mm
Steering System	Mechanical Steering	
Theoretical Max. Speed	Forward	26.9km/h
	Reverse	9.2km/h
Linkage Type	Three-point Linkage	
PTO Speed	540rpm	
Drawbar Pull	3.1/3.5/3.7/3.9kN	
Net. Weight	770/810/830/850kg	
Packing Method	2units/Iron frame	
Container Loading Quantity	10units/20GP 22units/40HC	



XINGTAI AGRICULTURAL MACHINERY CO., LTD



MODEL : XT-244

Xingtai XT-244: The Ultimate 24HP Compact Tractor

- * Robust Power: 24HP 3-cylinder diesel engine with 4WD and a (6+2) direct gear transmission—no belt slippage.
- * Built Tough: Durable structure designed to effortlessly handle rugged terrains and heavy loads.
- * Easy Ownership: Simple design ensures low maintenance costs and easy repairs.
- * Top Value: Featuring an exclusive XT rear axle, it offers the market's best balance of reliability and price.

The Xingtai XT-244 is more than just a tractor; it is a best-selling workhorse that offers the perfect balance of power, durability, and high cost-performance. Its superior gear-drive system and exclusive XT rear axle make it the most reliable and valuable 24HP 4WD compact tractor on the market today.



XINGTAI AGRICULTURAL MACHINERY CO., LTD

MODEL : XT-244

Xingtai Series Tractor XT-244		
Specification		
Model	XT-244	
Drive Type	All Wheel Drive (4x4)	
Gearbox Type	XT	
Transmission Type	6 Forward & 2 Reverse gears	
Engine	Model	KM385BT
	Type	Diesel , Vertical , 3-Cylinder , 85mm-Bore , 4-Stroke , Water-Cooled
	Rated Speed	2350rpm
	12-hour Rated Power	17.6kW
	Displacement	1.532L
	Emission	Stage-2
	Starting System	Electric
Clutch Type	9-inch Single-stage Clutch	
Overall Dimensions	Length	2970mm
	Width	1310mm
	Height	1970mm
Wheelbase	1630mm	
Wheel Size	Front Wheel	6.00-14
	Rear Wheel	9.50-20
Wheel Track	Front Wheel	1030mm
	Rear Wheel	1070mm
Steering System	Hydraulic power steering	
Theoretical Max. Speed	Forward	26.9km/h
	Reverse	9.2km/h
Linkage Type	Three-point Linkage	
PTO Speed	540rpm/720rpm	
Drawbar Pull	5.4kN	
Net. Weight	1050kg	
Packing Method	2units / Iron frame	
Container Loading Quantity	22units/HC	



XINGTAI AGRICULTURAL MACHINERY CO., LTD



MODEL : XT-244L

The XT-244L is now equipped with the upgraded, more robust TY-model rear axle. This significant enhancement provides:

- * **Increased Durability:** Engineered for even greater strength, perfect for the demanding tasks expected of a leading middle tractor.
- * **Superior Reliability:** This reinforced axle ensures the XT-244L can handle the toughest jobs with complete confidence.

The XingTai XT-244L has rightfully earned its reputation as the go-to benchmark in the mini and middle tractor market. By combining proven reliability, strategic upgrades, and an unbeatable low cost of ownership, it offers the power of a mid-size tractor with the agility of a mini tractor. It is the perfect investment for smart farmers and operators who want a top-performing machine that is built to last.



XINGTAI AGRICULTURAL MACHINERY CO., LTD

MODEL : XT-244L

XingTai Series Tractor XT-244L		
Specification		
Model	XT-244L	
Drive Type	All Wheel Drive (4x4)	
Gearbox Type	TY	
Transmission Type	8 Forward & 2 Reverse gears	
Engine	Model	KM385BT
	Type	Diesel , Vertical , 3-Cylinder , 85mm-Bore , 4-Stroke , Water-Cooled
	Rated Speed	2350rpm
	12-hour Rated Power	17.6kW
	Displacement	1.532L
	Emission	Stage-2
	Starting System	Electric
Clutch Type	9-inch Single-stage Clutch	
Overall Dimensions	Length	3200mm
	Width	1460mm
	Height	2000mm
Wheelbase	1670mm	
Wheel Size	Front Wheel	6.00-16
	Rear Wheel	9.50-24
Wheel Track	Front Wheel	1230mm
	Rear Wheel	1250mm
Steering System	Hydraulic power steering	
Theoretical Max. Speed	Forward	26.9km/h
	Reverse	9.2km/h
Linkage Type	Three-point Linkage	
PTO Speed	540rpm/720rpm	
Drawbar Pull	6.9kN	
Net. Weight	1300kg	
Packing Method	2units / Iron frame	
Container Loading Quantity	18units / 40HC	



XINGTAI AGRICULTURAL MACHINERY CO., LTD



MODEL : XT-244C

Discover the XT-244C, the best-selling model that has set the new standard in the compact tractor category.

- * Enhanced Operator Comfort (Upgraded Cabin)
- * Flexible Power Options (24HP & 25HP)
- * Simple, Low-Cost Maintenance
- * Upgradable Heavy-Duty Lifting System
- * Proven 4WD Performance

Combining robust power, upgraded comfort, and unmatched value, the XT-244C is more than just a tractor—it's a smart investment for your farm's future. Its status as a market benchmark is well-earned through thousands of satisfied users.



XINGTAI AGRICULTURAL MACHINERY CO., LTD

MODEL : XT-244C

XingTai Series Tractor XT-244C		
Specification		
Model	XT-244C	
Drive Type	All Wheel Drive (4x4)	
Gearbox Type	TV	
Transmission Type	8 Forward & 2 Reverse gears	
Engine	Model	KM385BT
	Type	Diesel , Vertical , 3-Cylinder , 85mm-Bore , 4-Stroke , Water-Cooled
	Rated Speed	2350rpm
	12-hour Rated Power	17.6kW
	Displacement	1.532L
	Emission	Stage-2
	Starting System	Electric
Clutch Type	9-inch Single-stage Clutch	
Overall Dimensions	Length	3200mm
	Width	1470mm
	Height	2350mm
Wheelbase	1710mm	
Wheel Size	Front Wheel	6.00-16
	Rear Wheel	9.50-24
Wheel Track	Front Wheel	1230mm
	Rear Wheel	1250mm
Steering System	Hydraulic power steering	
Linkage Type	Three-point Linkage	
PTO Speed	540rpm/720rpm	
Drawbar Pull	7.2kN	
Net. Weight	1600kg	
Packing Method	1units/Iron frame	
Container Loading Quantity	8units/40HC	



XINGTAI AGRICULTURAL MACHINERY CO., LTD



MODEL : XT-304C

- * **Upgraded Power & Enhanced Comfort:** Building on the success of previous models, the XT-304C boasts increased horsepower for more demanding tasks. The enhanced cabin design significantly improves operator comfort, reducing fatigue during long hours in the field.
- * **Low-Cost & Accessible Maintenance:** Maximize your uptime and minimize operational costs. The XT-304C is engineered with easily accessible and highly affordable spare parts, making routine service and repairs both simple and economical.
- * **Upgradable Heavy-Duty Hydraulics:** For superior implement control, the standard three-point linkage can be upgraded to a powerful forced-lifting and forced-lowering system, allowing it to handle heavier, modern attachments with precision and ease.
- * **Proven Market Leader:** The XT-304C isn't just a new model; it's a proven performer. It has earned its reputation as the go-to benchmark in the small tractor category, trusted by thousands of users for its unwavering reliability.



XINGTAI AGRICULTURAL MACHINERY CO., LTD

MODEL : XT-304C

XingTai Series Tractor XT-304C		
Specification		
Model	XT-304C	
Drive Type	All Wheel Drive (4x4)	
Gearbox Type	TY	
Transmission Type	8 Forward & 2 Reverse gears	
Engine	Model	LL385BT
	Type	Diesel , Vertical , 3-Cylinder , 85mm-Bore , 4-Stroke , Water-Cooled
	Rated Speed	2350rpm
	12-hour Rated Power	22.1kW
	Displacement	1.6L
	Emission	Stage-2
	Starting System	Electric
Clutch Type	9-inch Single-stage Clutch	
Overall Dimensions	Length	3200mm
	Width	1470mm
	Height	2350mm
Wheelbase	1710mm	
Wheel Size	Front Wheel	6.00-16
	Rear Wheel	9.5-24
Wheel Track	Front Wheel	1230mm
	Rear Wheel	1250mm
Steering System	Hydraulic power steering	
Linkage Type	Three-point Linkage	
PTO Speed	540rpm/720rpm	
Drawbar Pull	7.4kN	
Net. Weight	1650kg	
Packing Method	1units/Iron frame	
Container Loading Quantity	8units/40HC	



XINGTAI AGRICULTURAL MACHINERY CO., LTD



MODEL : XT-504C

We listened to the market's demand for a stronger, more adaptable machine. The XT-504C delivers on these needs with significant engineering enhancements:

- * Reinforced Drivetrain (TE Gearbox & Rear Axle).
- * Expanded 50HP Working Range.
- * Multi-Purpose Adaptability.

For machinery dealers, the XT-504C represents a high-value opportunity. It targets the "sweet spot" of the market—customers looking for a 50 hp compact tractor for sale that is tough enough for commercial use but affordable enough for small-to-medium farms.



XINGTAI AGRICULTURAL MACHINERY CO., LTD

MODEL : XT-504C

XingTai Series Tractor XT-504C		
Specification		
Model	XT-504C	
Drive Type	All Wheel Drive (4x4)	
Gearbox Type	TE & Shuttle Gearbox	
Transmission Type	8 Forward & 8 Reverse gears	
Engine	Model	KM495BT
	Type	Diesel , Vertical , 4-Cylinder , 95mm-Bore , 4-Stroke , Water-Cooled
	Rated Speed	2400rpm
	12-hour Rated Power	36.8kW
	Displacement	2.8L
	Emission	Stage-2
	Starting System	Electric
Clutch Type	10-inch Single-stage Clutch	
Overall Dimensions	Length	3490mm
	Width	1710mm
	Height	2630mm
Wheelbase	1870mm	
Wheel Size	Front Wheel	7.50-16
	Rear Wheel	11.2-28
Wheel Track	Front Wheel	1230mm
	Rear Wheel	1250mm
Steering System	Hydraulic power steering	
Linkage Type	Three-point Linkage	
PTO Speed	540rpm/760rpm	
Drawbar Pull	9.5kN	
Net. Weight	2070kg	
Packing Method	1units/Iron frame	
Container Loading Quantity	7units/40HC	



XINGTAI AGRICULTURAL MACHINERY CO., LTD



MODEL : XT-1004C

The XT-1004C has been extensively re-engineered to handle heavier loads and more complex implements than ever before. It offers distinct competitive advantages:

- * Robust TB Chassis & Reinforced Rear Axle.
- * 100HP of Unrelenting Power.
- * Superior 12F+12R Shuttle Shift Transmission.
- * Maximized Traction and Stability.

In the global market for a 100 hp 4wd agricultural tractor, the XT-1004C is unrivaled in cost-performance. It bridges the gap between economy models and premium brands, offering the heavy lifting capabilities of a high-end machine at a price point that guarantees excellent margins for our partners. It is the ideal choice for farmers expanding their operations and dealers looking to capture the heavy-equipment segment.



XINGTAI AGRICULTURAL MACHINERY CO., LTD

MODEL : XT-1004C

XingTai Series Tractor XT-1004C		
Specification		
Model	XT-1004C	
Drive Type	All Wheel Drive (4x4)	
Gearbox Type	TB & Shuttle Gearbox	
Transmission Type	12 Forward & 12 Reverse gears	
Engine	Model	YN38CCF4
	Type	Diesel , Vertical , 4-Cylinder , 4-Stroke , Water-Cooled
	Rated Speed	2400rpm
	12-hour Rated Power	74kW
	Emission	Stage-2
	Starting System	Electric
Clutch Type	11-inch Single-stage Clutch	
Overall Dimensions	Length	4100mm
	Width	1850mm
	Height	2710mm
Wheelbase	2100mm	
Wheel Size	Front Wheel	8.3-24
	Rear Wheel	11-32
Wheel Track	Front Wheel	1310mm
	Rear Wheel	1400mm
Steering System	Hydraulic power steering	
Theoretical Max. Speed	Forward	33.59km/h
	Reverse	13km/h
Linkage Type	Three-point Linkage	
PTO Speed	540rpm/760rpm	
Net. Weight	3200kg	
Packing Method	1units/Iron frame	